



CLEAR SIGHT

Enhance your view
with anti-reflective glass

AGC

Your Dreams, Our Challenge

Clearsight: AGC's exclusive anti-reflective glass

The special anti-reflective coating minimises glare and reduces light reflection.

Compared to conventional float glass, Clearsight offers greater clarity and improved vision through the glass.

With Clearsight



Realistic Rendering*

Without Clearsight



* Realistic rendering based on Clearsight - Double Glazing
(see values in the Technical Specifications section)

Dive into the view

In windows, Clearsight delivers superb transparency and higher light transmission, making it the perfect choice when an optimal view is required.

At night, one can benefit from the reduced internal reflection, enjoying the outside view.



Realistic Rendering*



* Realistic rendering based on Clearsight - Double Glazing
(see values in the Technical Specifications section)

Enhance your view with anti-reflective glass

CLEARSTIGHT

What's so special about it?


What does this mean for you?

- Anti-reflective coating**
 - Significantly lower light reflection: $\leq 1\%$ (with double sided anti-reflective coating)
 - Optimal vision and clarity
 - Enhanced contrast for objects in display applications
 - Better view from inside and outside
- Magnetron sputtering technology**
 - Durable coating suitable for both interior and exterior applications
 - Abrasion resistance
- Higher light transmission**
 - More light entering the building
 - Better aesthetics
- One product, two uses**
 - Heat-treated or annealed
 - Same energy and light transmission in heat-treated and annealed version
 - Similar aesthetics before and after heat treatment

Visible Light Reflection (LR)



Conventional Float Glass: $\leq 8\%$



Clearstight: $\leq 1\%$

CLEARLIGHT

Clearsight - Single Glazing (monolithic)

		Clearlite	Clearsight (monolithic)			
Thickness (mm)		4	4	5	6	8
AR coating position		-	#1 & #2			
Light performance	LT (%)	90	99	98	98	98
	LR (%)	8	≤ 1	≤ 1	≤ 1	≤ 1
Energy performance	SF (%)	88	84	84	83	83
	EA (%)	5	3	3	4	4
	Sc	1.01	0.96	0.96	0.96	0.95
Ug value	W/m²K	5.8	5.8	5.7	5.7	5.6

Stratobel Clearsight - Laminated

		Stratobel 44.2 ¹	Stratobel Clearsight (laminated)		
Thickness (mm)		44.2 ¹	44.2 ¹	66.2 ²	88.2 ³
AR coating position		-	#1 & #4		
Light performance	LT (%)	89	98	98	97
	LR (%)	8	≤ 1	≤ 1	≤ 1
Energy performance	SF (%)	80	79	79	78
	EA (%)	17	10	11	13
	Sc	0.92	0.91	0.90	0.90
Ug value	W/m²K	5.5	5.5	5.4	5.3

1) 44.2 refers to 4 mm Clearsight / 0.76 mm PVB / 4 mm Clearsight

2) 66.2 refers to 6 mm Clearsight / 0.76 mm PVB / 6 mm Clearsight

3) 88.2 refers to 8 mm Clearsight / 0.76 mm PVB / 8 mm Clearsight

Specifications

CLEAR SIGHT

Clearsight - Double Glazing*

		Normal DGU iplus 1.1 pos.3	Clearsight DGU with iplus 1.1 pos.3
Composition		4-16 - Argon 90% - 44.2	4-16 - Argon 90% - 44.2
AR coating position		-	#1 & #2 & #4
Light performance	LT (%)	80	92
	LR (%)	12	2
Energy performance	SF (%)	64	66
	EA (%)	20	14
	Sc	0.73	0.76
Ug value	W/m ² K	1.1	1.1

Clearsight - Triple Glazing

		Normal TGU iplus 1.1 pos.2 and 5	Clearsight TGU iplus 1.1 pos.2 and 5
Composition		44.2 - 16 - Argon 90% - 6 - 16 - Argon 90% - 44.2	44.2 - 16 - Argon 90% - 6 - 16 - Argon 90% - 44.2
AR coating position		-	#1 & #3 & #4 & #6
Light performance	LT (%)	71	85
	LR (%)	15	4
Energy performance	SF (%)	47	53
	EA (%)	36	27
	Sc	0.54	0.61
Ug value	W/m ² K	0.6	0.6

* Realistic residential window rendering based on these values

Making glass invisible

Perfect for shop window applications

Clearsight is the perfect glass for shop windows, showcases and museum displays. Its reflection is highly reduced and faithfully reveals the colour and appearance of items on display.

With Clearsight



Realistic Rendering*

Without Clearsight



* Realistic rendering based on Clearsight - Double Glazing
(see values in the Technical Specifications section)

Processing options

Safety	Lamination (PVB or EVA)
	Can be heat treated
Cutting	Straight or circular
Shaping and edge finishing	Edge grinding
	Grinding
	Drilling
	Notches
Insulated glazing units	Double and triple glazing

AVAILABILITY

Clearsight is produced with both single or double sided anti-reflective coating.

THICKNESSES

- Clearsight Single-sided is available in standard thicknesses: 4, 5, 6, and 8 mm.
- Clearsight Double-sided is available in standard thicknesses: 4, 6 and 8 mm.
- Stratobel Clearsight Double-sided in 44.2, 55.4, 66.2 and 66.4.
- Other thicknesses (3, 10, 12 mm) on request.

DIMENSIONS

2250 x 3210 mm, 2550 x 3210 mm and 6000 x 3210 mm.

Shelf life: unlimited.



Clearsight is Cradle to Cradle
Certified™ Silver

AGC GLASS EUROPE

UNITED KINGDOM - AGC Glass UK - T +44 1788 53 53 53 - sales.uk@eu.agc.com
OTHER COUNTRIES - AGC Glass Europe - T +32 2 409 30 00 -
sales.headquarters@eu.agc.com - AGC Glass Europe has representatives worldwide
See www.agc-yourglass.com for further addresses

