

LED EMERGENCY LIGHTING



LEDOS



WHEN THE POWER IS OUT, THAT'S WHEN WE SHINE.

LEDOS Emergency Lighting products offer efficiency, quality, affordability, and universal designs that are ideal for all indoor applications.



Efficiency

Using the latest in LED technology, LEDOS achieves high brightness and low power consumption with a 50,000 hour bulb rating.

Quality

Built with a flame rated thermoplastic housing that provides corrosion resistance & durability. Standard 3 year warranty.

Affordability

No bulb replacement for the complete life-span of the product. Fewer service calls, energy efficient, lower cost of ownership.

Universal Design

Versatility ranging from 120/277 VAC universal input voltages, to ceiling, wall, or end mounting options.

LEDOS

Safer • Smarter • More Liveable Buildings

LD-201 R/G

LED Exit Sign Twin Spot Combo



EXIT / GOMBO EXIT

FEATURES	
Power Exit	4W / 8W
Power Emergency	2 x 2.4W / 2 x 4W
Lamp Type	LED
Input Voltage	120/277 VAC
Frequency	60 Hz
LED Type	SMD LED
Battery Type	Ni-Cd
Working Time	90 Minutes
Charging Time	15-24 Hours



DESCRIPTION

- Injection-molded thermoplastic ABS housing
- UL-94V-0 flame rating, fire-retardant
- Wall and ceiling mounting
- Input Voltage: 120/277VAC 60Hz
- Nickel Cadmium Battery
- Test switch and charge indicator light
- Overcharge & Over-discharge protection
- Backup time: ≥ 90 minutes
- Conversion time: < 0.2 second
- IP Class: IP20
- Insulation: II, Range: 80m2
- Operating Temperature: $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$

TECHNICAL DRAWING

