

LED EMERGENCY LIGHTING



LEDOS



WHEN THE POWER IS OUT, THAT'S WHEN WE SHINE.

LEDOS Emergency Lighting products offer efficiency, quality, affordability, and universal designs that are ideal for all indoor applications.



Efficiency

Using the latest in LED technology, LEDOS achieves high brightness and low power consumption with a 50,000 hour bulb rating.

Quality

Built with a flame rated thermoplastic housing that provides corrosion resistance & durability. Standard 3 year warranty.

Affordability

No bulb replacement for the complete life-span of the product. Fewer service calls, energy efficient, lower cost of ownership.

Universal Design

Versatility ranging from 120/277 VAC universal input voltages, to ceiling, wall, or end mounting options.

LEDOS

Safer • Smarter • More Liveable Buildings

LD-111

Emergency Light



FEATURES	
Power (W)	4 W
Lamp Type	6500K LED
Input Voltage	220/240 VAC
Frequency	60 Hz
LED Type	SMD
Battery Type	Ni-Cd
Working Time	90 Minutes
Charging Time	15-24 Hours



DESCRIPTION

- Injection-molded thermoplastic ABS housing
- Wall and ceiling mounting
- Switchable input Voltage: 220/240VAC
- Super bright SMD LED
- Lamps for Emergency Mode
- Test switch and charge indicator light
- Overcharge & Over-discharge protection
- Backup time: ≥ 90 minutes
- Conversion time: < 0.2 second
- IP Class: IP54
- Insulation: II, Range: 80m² / 860sq.ft
- Operating Temperature:
0 °C ~ 40 °C / 32 °F ~ 104 °F